



DESCRIPTION

The Beak Ceiling/Wall's adjustable cylinder directs and projects a beam of direct light. Its smooth, burnished brass finish is accented by knurling on the head, adding visual rhythm to the structure. Also available in a Flat version with a reducedthickness canopy, Beak Ceiling/Wall can be installed on both walls and ceilings, making it ideal for contract settings. Beak is also available in Floor, Table, and Suspension versions.

PRODUCTS DETAILS

FUNCTION CEILING/WALL LOCATION INTERIOR

LIGHT EMISSION **DIRECTIONAL LIGHT**

LIGHT SOURCE $\mathsf{COB}\,\mathsf{LED}\,\mathsf{CLU703}\,\mathsf{6W}\,\mathsf{724Im}\,\mathsf{700mA}\,\mathsf{9V}\,\mathsf{CRI90}\,\mathsf{2700}^\circ\mathsf{K}$

ENERGY EFFICIENCY

110 - 120 V / 220 - 240 V RATED VOLTAGE

FREQUENCY 50 - 60Hz

SUPPLY BEAK CEILING/WALL TERMINAL BLOCK

BEAK CEILING/WALL FLAT

REMOTE TERMINAL BLOCK

LENS SPOT BEAM 18° - 36° - 60°

BEAK CEILING/WALL: DALI OR TRIAC DIMMING KIT AVAILABLE UPON REQUEST.

BEAK CEILING/WALL FLAT: DALI OR TRIAC REMOTE DIMMING KIT AVAILABLE UPON REQUEST.

CERTIFICATION









MATERIALS

STRUCTURE

M11 LIGHT BURNISHED BRASS M12 DARK BURNISHED BRASS

PACKAGE

QTY

DIMENSIONS

NET WEIGHT

GROSS WEIGHT

TOTAL VOL.

DIMENSIONS

BEAK CEILING/WALL

Ø9 cm (3"5)

STANDARD

21cm (8"3)



J-BOX KIT



Ø 14 cm (5"5)



BEAK CEILING/WALL FLAT

Ø8 cm (3"1)

STANDARD

18 cm (7")







J-BOX KIT



Ø11cm (4"3)



