



DESCRIPTION

Orthogonal lines intertwine in a clear, sharply evocative construction, where an elegant intersection of tubular bodies defines the structure of Kitami LED. Geometric and essential, this version is the revisitation of the Kitami collection, evolving the play of light. The LED inserts, integrated directly into the rods, replace the previous glass light terminals, creating atmospheres of direct light. The metal structure ensures dynamism and solidity, with an unpredictable geometric precision of shapes and materials.

PRODUCTS DETAILS

FUNCTION	SUSPENSION
LOCATION	INTERIOR
LIGHT EMISSION	DIFFUSED LIGHT
LIGHT SOURCE	KITAMI LED SUSPENSION - L STRIP LED 11.5W/m 2700°K 2000lm/m CRI 90+ 24Vdc TOT. = 29W 5000lm
RATED VOLTAGE	110 - 120V / 220 - 240V
FREQUENCY	50 - 60Hz
SUPPLY	TERMINAL BLOCK
BALLAST	BALLAST INCLUDED

DALI OR TRIAC DIMMING KIT AVAILABLE UPON REQUEST.

CERTIFICATION



MATERIALS

STRUCTURE	
M04	POLISHED BLACK NICKEL
M05	POLISHED GOLD
M07	MATTE BLACK NICKEL
M11	LIGHT BURNISHED BRASS

PACKAGE

QTY	DIMENSIONS	NET WEIGHT	GROSS WEIGHT	TOTAL VOL.
	KITAMI LED SUSPENSION - L			
-	-	-	-	-

DIMENSIONS

KITAMI LED SUSPENSION - L

